

PROTECT 200

DECLARATION OF PERFORMANCE

No. **C00065-CPR-2030952**

1. Unique identification code of the product type: **PROTECT 200**

2. Intended use/s: **Surface protection products, hydrophobic impregnation**

3. Manufacturer: **DOMOCHEMICAL S.A.
Papanikoli 40
15232 Chalandri, Athens
+30 210 6893954
novamix@novamix.gr
www.novamix.gr**

4. Authorised representative:

5. System/s of AVCP: **System 2+**

- 6a. Harmonised standard: **EN 1504-2:2004**

- Notified body/ies: **1128**

PROTECT 200

7. Declared performance/s:

Essential characteristics	Performance	Harmonized Technical Specification
Depth of penetration	Class II: ≥ 10 mm	
Water absorption and resistance to alkali as:		
- absorption ratio compared with the untreated specimen	< 7,5%	
- absorption ratio < 10 % after immersion in alkali solution	< 10%	EN 1504-2:2004
Drying rate for hydrophobic impregnation	Class I: > 30 %	
Dangerous substances	Comply with 5.3	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Thiva, 14/12/2020


Dr. Plumis Papavassiliou
R&D/QC Manager

End of information as required by Regulation (EU) No 305/2011 & 574/2014

PROTECT 200

 1128
DOMOCHEMICAL S.A. PAPANIKOLI 40, 15232 CHALANDRI, ATHENS 14
1128-CPR-0416/1
DoP No. C00065-CPR-2030952 PROTECT 200 EN 1504-2
Surface protection products, hydrophobic impregnation
Depth of penetration: Class II: ≥ 10 mm
Water absorption and resistance to alkali as: absorption ratio $< 7,5$ % compared with the untreated specimen absorption ratio < 10 % after immersion in alkali solution
Drying rate for hydrophobic impregnation: Class I: > 30 %
Dangerous substances comply with 5.3