

SC ELASTIC

DECLARATION OF PERFORMANCE

No. **C00068-CPR-2130702**

1.	Unique identification code of the product type:	SC ELASTIC
2.	Intended use/s:	Surface protection product - Coating Principle 2(Moisture control) Method 2.3 and Principle 8(Increasing resistivity) Method 8.3
3.	Manufacturer:	DOMOCHEMICAL S.A. Papanikoli 40 15232 Chalandri, Athens +30 210 6893954 novamix@novamix.gr www.novamix.gr
4.	Authorised representative:	
5.	System/s of AVCP:	System 2+
6a.	. Harmonised standard:	EN 1504-2:2004
	Notified body/ies:	1128



SC ELASTIC

7. Declared performance/s:

Essential characteristics	Performance	Harmonized Technical Specification
Capillary absorption and permeability to water	$W < 0.1 \text{ kg/m}^2 \text{h}^{0,5}$	_
Adhesion by Pull-off test	≥ 1.5 MPa	
Permeability to water vapour	Class I, $S_D < 5m$	EN 1504-2:2004
Dangerous substances	comply with 5.3	
Reaction to fire	Class F	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thiva, 29/01/2021

Dr. Plumis Papavassiliou R&D/QC Manager



SC ELASTIC



1128

ΔΟΜΟΧΗΜΙΚΗ A.B.E.E.ΠΑΠΑΝΙΚΟΛΗ 40, 15232 ΧΑΛΑΝΔΡΙ, ΑΘΗΝΑ **DOMOCHEMICAL S.A**PAPANIKOLI 40, 15232 CHALANDRI, ATHENS

14 1128-CPR-0416/1

EN 1504-2:2004 SC ELASTIC DoP No. C00068-CPR-2130702

Προϊόν επιφανειακής προστασίας – Επίστρωση	Surface protection product - Coating	Επίδοση Performance
Τριχοειδής απορροφητικότητα και υδατοπερατότητα	Capillary absorption and permeability to water	W < 0.1 kg/m ² h ^{0,5}
Αντοχή σε πρόσφυση	Adhesion by Pull-off test	≥ 1.5 MPa
Διαπερατότητα σε υδρατμούς	Permeability to water vapour	Class I, S _D < 5m
Επικίνδυνες ουσίες	Dangerous substances	Comply with 5.3
Αντίδραση στη φωτιά	Reaction to fire	Class F