

ALKALINE CLEANER

Powerful alkaline detergent

- ▷ **For deep cleaning of oil stains and grease**
 - ▷ **Highly concentrated and effective**
 - ▷ **Suitable for tiles, concrete and mineral surfaces**
 - ▷ **Doesn't damage or alters colored joints between tiles**
 - ▷ **Removes persistent and difficult stains**
-

Description

ALKALINE CLEANER is a highly concentrated professional alkaline cleaner for removing greasy stains from concrete, tiles, natural stones and acid-sensitive surfaces. It has high penetrating capacity, effectively removes greasy pollutants in depth and restores original shade and shine.

Uses

Suitable for cleaning concrete, tiles and natural stone from:

- Oily residues and stains, grease
- Black shoe marks, household stains
- Liquid and natural protective floor waxes

For surfaces such as:

- Ceramic and Gres porcelain tiles
- Concrete, microcement coatings
- Mineral, alkali resistant coverings

Suitable for application in:

- Houses
 - Public areas such as restaurants, hotels, hospitals
 - Industrial areas and office buildings
-

Technical Data

Product Identity

Form	Liquid
Color	Transparent
Density	1,07 ± 0,02 kg/l
pH	12,5 ± 0,2

Application procedure

Application Apply ALCALINE CLEANER diluted in water 1:10 to 1:20 depending on the type of surface and dirt on the surface to be cleaned and let the product act for 5 - 10 minutes. Then rub lightly with a brush or sponge. At the end of the process, in all cases, carefully rinse the surface with plenty of water. In highly persistent or deeply impregnated stains, repeat the procedure. For removal of water based liquid waxes and natural floor waxes, dilute 1: 5 to 1:10 When applied to polished surfaces, it is recommended to prepare a test area in a small, not visible part of the surface.

Recommendations

- Do not apply:
- On alkali sensitive surfaces
- On polished surfaces without preparing a test area
- For removal of cement traces
- On any surface before consulting the safe use instructions on the label before using
- Keep out of reach of children

Consumption General deep cleaning 1L/200m² diluted 1:20
Removal of liquid waxes, natural floor waxes etc. 1L/20m² diluted 1:5

Storage ALCALINE CLEANER remains stable for at least 12 months from production date, in its sealed original packing, stored in dry conditions and temperatures between +5°C and +35°C.

Packaging Containers of 1L and 5L.

Safety Instructions For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety related data.

Legal notes The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown.

In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice.

Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr