

EPO FLUID

DECLARATION OF PERFORMANCE

No. **C04801-CPR-2220810**

1. Unique identification code of the product type: **EPO FLUID**

2. Intended use/s: **Anchoring product for reinforcing steel bars**

3. Manufacturer: **DOMOCHEMICAL S.A.
Papanikoli 40
15232 Chalandri, Athens
+30 210 6893954
novamix@novamix.gr
www.novamix.gr**

4. Authorised representative:

5. System/s of AVCP: **System 4**

- 6a. Harmonised standard: **EN 1504-6:2006**

- Notified body/ies: **-**

EPO FLUID

7. Declared performance/s:

Essential characteristics	Performance	Harmonized Technical Specification
Pull-out strength	Displacement $\leq 0,6$ mm at load of 75 KN	EN 1504-6:2006
Chloride ion content	≤ 0.05 %	
Durability/Creep under tensile load	≤ 0.6 mm at 50 kN for 3 months	
Glass transition temperature	$\geq 45^{\circ}\text{C}$	
Reaction to fire	Euroclass F	
Dangerous substances	Comply with 5.4	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thiva, 26/01/2022


Dr. Plumis Papayassiliou
R&D/QC Manager

End of information as required by Regulation (EU) No 305/2011 & 574/2014

EPO FLUID

CE	
15 DOMOCHEMICAL S.A PAPANIKOLI 40, 15232 CHALANDRI, ATHENS	
DoP No.: C04801-CPR-2220810 EPO FLUID EN 1504-6:2006	
Anchoring product for reinforcing steel bars	
Pull-out strength:	Displacement \leq 0,6 mm at load of 75 KN
Chloride ion content:	\leq 0.05 %
Durability/Creep under tensile load:	\leq 0.6 mm at 50 kN for 3 months
Glass transition temperature:	\geq 45°C
Reaction to fire:	Euroclass F
Dangerous substances:	Comply with 5.4