

FINE RENDER

DECLARATION OF PERFORMANCE

No. **C06861-CPR-2150204**

1. Unique identification code of the product type: **FINE RENDER**
2. Intended use/s: **General purpose rendering mortar (GP) for internal and external use**
3. Manufacturer: **DOMOCHEMICAL S.A.
Papanikoli 40
15232 Chalandri, Athens
+30 210 6893954
novamix@novamix.gr
www.novamix.gr**
4. Authorised representative:
5. System/s of AVCP: **System 4**
- 6a. Harmonised standard: **EN 998-1:2016**
- Notified body/ies: **-**

FINE RENDER

7. Declared performance/s:

| Characteristics | Performance | Harmonized Technical Specification |
|--|---------------------------------|------------------------------------|
| Reaction to fire | Class A1 | |
| Compressive strength | CS IV | |
| Adhesion | ≥ 0.6 N/mm ² , FP: B | |
| Capillary water absorption | W _c 1 | EN 998-1:2016 |
| Water vapour permeability coefficient (μ) | ≤ 20 | |
| Thermal conductivity mean λ _{10,dry,mat} values | 0.45 W/mK | |
| Durability | Comply with 5.3.2 | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thiva, 05/03/2021



Dr. Plumis Papavassiliou
R&D/QC Manager

End of information as required by Regulation (EU) No 305/2011 & 574/2014

FINE RENDER



14

ΔΟΜΟΧΗΜΙΚΗ Α.Β.Ε.Ε.
ΠΑΠΑΝΙΚΟΛΗ 40, 15232 ΧΑΛΑΝΔΡΙ, ΑΘΗΝΑ
DOMOCHEMICAL S.A
ΡΑΡΑΝΙΚΟΛΙ 40,15232 CHALANDRI, ATHENS

EN 998-1:2016
FINE RENDER
DoP No.: C06861-CPR-2150204

Επίχρισμα γενικής χρήσης (GP) για εσωτερική και εξωτερική εφαρμογή
General purpose rendering mortar (GP) for internal and external use

| | | |
|---|---|---------------------------------------|
| Αντίδραση στη φωτιά | Reaction to fire | A1 |
| Θλιπτική αντοχή | Compressive strength | CS IV |
| Πρόσφυση | Adhesion | ≥ 0,6 N/mm ² , FP: B |
| Τριχοειδής απορρόφηση νερού | Capillary water absorption | W _{c1} |
| Συντελεστής διάχυσης υδρατμών (μ) | Water vapour permeability coefficient (μ) | ≤ 20 |
| Συντελεστής θερμικής αγωγιμότητας λ _{10,ξηρό} | Thermal conductivity mean λ _{10,dry,mat} values | 0,45 W/mK |
| Ανθεκτικότητα | Durability | Σύμφωνα με 5.3.2 Comply with 5.3.2 |