

SC 200 PENETRATE

DECLARATION OF PERFORMANCE

No. **C07605-CPR-2030402**

- | | |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Unique identification code of the product type: | SC 200 PENETRATE |
| 2. Intended use/s: | Surface protection product - Coating
Principle 2(Moisture control) Method 2.3 and Principle 8(Increasing resistivity) Method 8.3 |
| 3. Manufacturer: | DOMOCHEMICAL S.A.
Papanikoli 40
15232 Chalandri, Athens
+30 210 6893954
novamix@novamix.gr
www.novamix.gr |
| 4. Authorised representative: | |
| 5. System/s of AVCP: | System 2+ |
| 6a. Harmonised standard: | EN 1504-2:2004 |
| Notified body/ies: | 1128 |

SC 200 PENETRATE


7. Declared performance/s:

Essential characteristics	Performance	Harmonized Technical Specification
Capillary absorption and permeability to water	$W < 0.1 \text{ kg/m}^2\text{h}^{0,5}$	EN 1504-2:2004
Adhesion by Pull-off test	$\geq 1.5 \text{ MPa}$	
Permeability to water vapour	Class I, $S_D < 5\text{m}$	
Dangerous substances	comply with 5.3	
Reaction to fire	Class F	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thiva, 02/11/2020


 Dr. Plumis Papavassiliou
 R&D/QC Manager

End of information as required by Regulation (EU) No 305/2011 & 574/2014

SC 200 PENETRATE



1128

ΔΟΜΟΧΗΜΙΚΗ Α.Β.Ε.Ε.

ΠΑΠΑΝΙΚΟΛΗ 40, 15232 ΧΑΛΑΝΔΡΙ, ΑΘΗΝΑ

DOMOCHEMICAL S.A

ΠΑΡΑΝΙΚΟΛΙ 40, 15232 CHALANDRI, ATHENS

14

1128-CPR-0416/1

EN 1504-2:2004

SC 200 PENETRATE

DoP No. C07605-CPR-2030402

Προϊόν επιφανειακής προστασίας – Επίστρωση	Surface protection product - Coating	Επίδοση Performance
Τριχοειδής απορροφητικότητα και υδατοπερατότητα	Capillary absorption and permeability to water	$W < 0.1 \text{ kg/m}^2\text{h}^{0,5}$
Αντοχή σε πρόσφυση	Adhesion by Pull-off test	$\geq 1.5 \text{ MPa}$
Διαπερατότητα σε υδρατμούς	Permeability to water vapour	Class I, $S_D < 5\text{m}$
Επικίνδυνες ουσίες	Dangerous substances	Comply with 5.3
Αντίδραση στη φωτιά	Reaction to fire	Class F