

NOVACOLOR OXIDE

Pigments in powder form

- ▷ **Suitable for internal and external areas**
- ▷ **Resistant to UV radiation**
- ▷ **Excellent alkaline resistance**

Description

NOVACOLOR OXIDE are pigments in powder form with high color and weathering fastness. Suitable for the coloration of a wide variety construction materials such as plaster, self-leveling screeds and mortars manufactured with NOVACEM CREATIVE & NOVACEM CREATIVE FLOOR.

Technical Data

Product Identification

Consistency	Powder
Color	Depending on the packaging indication
Shades	White, black, brown, red, green, blue

Application Procedure

Application

Add NOVACOLOR OXIDE to the amount of water required by each mortar, then the material and stir well to achieve the desired color shade.

Recommendations

- Do not exceed dosages 5% by weight
 - Careful stirring is recommended to achieve the color shade
 - It is recommended that the application be made by a professional user
-

Storage

NOVACOLOR OXIDE remains stable for 5 years from the production date in the original sealed packaging stored in a dry place and temperature between +5°C and +35°C.

Packaging

Plastic buckets of 250 g.

Safety Instructions

For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety-related data.

Legal Notes

The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown.

In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied, as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice.

Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



SCAN ME

DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr