

NOVATHINNER PU

Universal solvent

▷ **Polyurethane varnishes and paints**

▷ **Epoxy systems**

Description NOVATHINNER PU is a special solvent suitable for epoxy or polyurethane paints, coatings or varnishes. Also suitable for cleaning surfaces and tools where the above coatings were used.

Uses NOVATHINNER PU is suitable for mixing with:

- PLANOFINISH PU 2KS & PLANOFINISH PU 2KS MAT
- PLANOFINISH PU 2KS & PLANOFINISH PU 2KS MAT varnishes when applied on natural stones and micro-cement mortars outdoors
- The PLANOFINISH PU 2KS varnish when applied on PLANOCOLOR PREMIUM SP for pool protection
- Compatible epoxy and polyurethane systems

Technical Data

Product Identity

Form	Liquid
Color	Transparent
Density	0,87 ± 0,05 kg/L

Recommendations

- Keep away from sources of ignition
- To remove paints or varnishes they must still be fresh
- Do not mix with PLANOCOLOR PU polyurethane binder
- In all cases of mixing check for compatibility
- The application is recommended by a professional user

Consumption	Depending on the type of application.
Storage	NOVATHINNER PU remains stable for at least 12 months from production date, in its sealed original packing, stored in dry conditions and temperatures between +5°C and +35°C.
Packaging	Containers of 1L and 5L.
Safety Instructions	For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety related data.

Legal notes

The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown.

In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied, as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice.

Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



SCAN ME

DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr