

# NOVACOL ULTRA GEL

## DECLARATION OF PERFORMANCE

No. **C09327-CPR-2000350**

1. Unique identification code of the product type: **NOVACOL ULTRA GEL**
  
2. Intended use/s: **Improved cementitious adhesive for internal and external tiling**
  
3. Manufacturer: **DOMOCHEMICAL S.A.  
Papanikoli 40  
15232 Chalandri, Athens  
+30 210 6893954  
novamix@novamix.gr  
www.novamix.gr**
  
4. Authorised representative:
  
5. System/s of AVCP: **System 3**
  
- 6a. Harmonised standard: **EN 12004:2007+A1:2012**
  
- Notified body/ies: **0437**

# NOVACOL ULTRA GEL

## 7. Declared performance/s:

Essential characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	
Release of dangerous substances	See MSDS	
Bond strength, as: - initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$	EN 12004:2007 +A1:2012
Durability, as: - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion strength after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thiva, 7/7/2020



Dr. Plumis Papayassiliou  
R&D/QC Manager

End of information as required by Regulation (EU) No 305/2011 & 574/2014

# NOVACOL ULTRA GEL



**20**

**ΔΟΜΟΧΗΜΙΚΗ Α.Β.Ε.Ε.**  
ΠΑΠΑΝΙΚΟΛΗ 40, 15232 ΧΑΛΑΝΔΡΙ, ΑΘΗΝΑ  
**DOMOCHEMICAL S.A**  
ΠΑΡΑΝΙΚΟΛΙ 40, 15232 CHALANDRI, ATHENS

**C09327-CPR-2000350**  
**NOVACOL ULTRA GEL**  
**EN 12004:2007 + A1:2012**  
**NB: 0437**

**Βελτιωμένη τσιμεντοειδής κόλλα για εσωτερική και εξωτερική χρήση**  
**Improved cementitious adhesive for internal and external tiling**

Αντίδραση στη φωτιά	Reaction to fire	Class E
Απελευθέρωση επικίνδυνων ουσιών	Release of dangerous substances	Βλέπε ΔΔΑ See MSDS
Πρόσφυση ως: - αρχική εφελκυστική αντοχή	Bond strength, as: - initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Ανθεκτικότητα για: - εφελκυστική αντοχή μετά από θερμική γήρανση - εφελκυστική αντοχή μετά από εμβάπτιση σε νερό - εφελκυστική αντοχή μετά από κύκλους ψύξης/απόψυξης	Durability, for: - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion strength after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$