

NOVACOL SUPER

DECLARATION OF PERFORMANCE

No. **C09461-CPR-2100260**

1. Unique identification code of the product type: **NOVACOL SUPER**

2. Intended use/s: **Improved cementitious adhesive for internal and external tiling**

3. Manufacturer: **DOMOCHEMICAL S.A.
Papanikoli 40
15232 Chalandri, Athens
+30 210 6893954
novamix@novamix.gr
www.novamix.gr**

4. Authorised representative:

5. System/s of AVCP: **System 3**

- 6a. Harmonised standard: **EN 12004:2007+A1:2012**

- Notified body/ies: **0437**

NOVACOL SUPER

7. Declared performance/s:

Essential characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class F	
Release of dangerous substances	See MSDS	
Bond strength, as: - initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$	EN 12004:2007 +A1:2012
Durability, as: - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion strength after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thiva, 11/12/2020



Dr. Plumis Papayassiliou
R&D/QC Manager

End of information as required by Regulation (EU) No 305/2011 & 574/2014

NOVACOL SUPER

CE		
21		
ΔΟΜΟΧΗΜΙΚΗ Α.Β.Ε.Ε. ΠΑΠΑΝΙΚΟΛΗ 40, 15232 ΧΑΛΑΝΔΡΙ, ΑΘΗΝΑ DOMOCHEMICAL S.A ΡΑΡΑΝΙΚΟΛΙ 40, 15232 CHALANDRI, ATHENS		
C09461-CPR-2100260 NOVACOL SUPER EN 12004:2007 + A1:2012 NB: 0437		
Βελτιωμένη τσιμεντοειδής κόλλα για εσωτερική και εξωτερική χρήση Improved cementitious adhesive for internal and external tiling		
Αντίδραση στη φωτιά	Reaction to fire	Class F
Απελευθέρωση επικίνδυνων ουσιών	Release of dangerous substances	Βλέπε ΔΔΑ See MSDS
Πρόσφυση ως: - αρχική εφελκυστική αντοχή	Bond strength, as: - initial tensile adhesion strength	≥ 1,0 N/mm ²
Ανθεκτικότητα για: - εφελκυστική αντοχή μετά από θερμική γήρανση - εφελκυστική αντοχή μετά από εμβάπτιση σε νερό - εφελκυστική αντοχή μετά από κύκλους ψύξης/απόψυξης	Durability, for: - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion strength after freeze/thaw cycles	≥ 1,0 N/mm ² ≥ 1,0 N/mm ² ≥ 1,0 N/mm ²