

PLANOCOLOR® GRANIT

PLANOCOLOR® GRANIT
CREATE WITH NATURE...



ART OF DESIGN PLANOCOLOR® GRANIT

PLANOCOLOR® GRANIT system provides the possibility to create uniform surface coverings with the minimum of thickness on walls, floors and ceilings, in the form of a 'stone carpet' floor or a quartz plaster.

STONE CARPET

PLANOCOLOR® GRANIT

Outdoor floors with a continuous quartz floor or 'stone carpet' appearance that are 'connected' with water elements and the rocky relief of the wider area.







QUARTZ PLASTERS

PLANOCOLOR® GRANIT

PLANOCOLOR® GRANIT quartz plasters, suitable for interior & exterior wall applications, function as a decorative 'shell' on every type of construction system: from traditional cement based substrate till ETICS or honeycomb panels.

The ability to cover even curved surfaces, to use natural stone or artificially coated granulates, provides unique design possibilities on both indoor and outdoor applications.





PLANOCOLOR® GRANULATES


SINGLE COLOR COATED NXD, NXG




WHITE
NX D 30 00



BLACK
NX D 30 19




CEMENTO
NX D 30 20




ANTRACITE
NX D 30 28




JASMINE
NX D 30 30



OCHRE
NX D 30 37



CORALLO
NX D 30 40



COTTO
NX D 30 45



CACAO
NX D 30 48




WARM RED
NX D 30 51




LIGHT PURPLE
NX D 30 62




PURPLE
NX D 30 67



BLUE
NX D 30 77




MIDNIGHT BLUE
NX D 30 78



GREEN
NX D 30 86




OLIVE GREEN
NX D 30 87




ORANGE
NX D 30 92



PINK
NX D 30 96



YELLOW
NX D 30 99



SILVER
NX G 30 111



GOLD
NX G 30 222



BRONZE
NX G 30 333

Due to printing process colors and appearance of applied products or packaging should be considered as indicative.



PLANOCOLOR® GRANULATES
**PREMIXED COATED
 NSD**



NS D 40 3162




NS D 40 3180




NS D 40 3231




NS D 40 3368




NS D 40 3464



NS D 40 3608



NS D 40 3703



NS D 40 3792

PLANOCOLOR® NATURAL UNCOATED GRANULATES
**PLAY WITH NATURE
 MQ, MR, S**



MILOS YELLOW
MR 60 50



MANI GREY LIGHT
MR 60 51



MANI GREY DARK
MR 80 51




CANDIA BROWN
MR 60 52




THIRA BLACK
MR 60 53



VOLCANO RED
MR 60 54




TINOS GREEN
MR 60 55



THASSOS WHITE
MR 70 00



COLORADO
MQ 30 14




RIVER GREY
MQ 50 18



S10



S30



S50




S70

PLANOCOLOR® GRANULATES


LIGHT WEIGHT COLORED IN THE MASS LC



GOLD
LC 60




GREEN
LC 60




DARK BLUE
LC 60



YELLOW
LC 60



RED
LC 60



BROWN
LC 60




ORANGE
LC 90


*Light weight granulates
in wide variety of colors.
Suitable for micro-
pebble coverings inside
swimming pools and for
terrazzo coverings.*

PLANOCOLOR® GRANULATES


PLAY WITH GLASS & LIGHT RC GLASS & LR




CRYSTAL CLEAR
RC GLASS 40 900




DARK BLUE
RC GLASS 40 910




LIGHT BLUE
RC GLASS 40 911




GREEN
RC GLASS 40 920




CRYSTAL GREEN
RC GLASS 40 922




GOLDEN BROWN
RC GLASS 90 950



FIRE RED
RC GLASS 40 990



GOLDEN YELLOW
RC GLASS 90 995



GREEN MIX
RC GLASS 4,0-8,0mm

APPLICATION DIAGRAMS FOR ▼ PLANOCOLOR® GRANIT

INTERNAL & EXTERNAL WALLS

SMOOTH SURFACES



15-60 MIN

PLANO CONTACT FAST
300-350 gr/m²

ABSORBENT SUBSTRATE



60 MIN

NOVAPRIMER
100-300ml/m²

or



1-15 MIN

PLANOPRIMER
100ml/m²



PLANOCOLOR® AC

+



PLANOCOLOR® GRANULATES

QUARTZ PLASTERS
FOR EXTERNAL
THERMAL INSULATION

NOTES

The consumption and time durations depend on the job-site conditions and the type of application.

APPLICATION DIAGRAMS FOR PLANOCOLOR® GRANIT

EXTERNAL FLOORS & WET AREAS

ABSORBENT SUBSTRATE



SC 200 PENETRATE
3,2 kg/m²

48 - 72 HOURS

VERTICAL SURFACES
As primer wet on wet -
no waiting



PLANOCOLOR® PU



PLANOEASY GRIP
5%

NON ABSORBENT SUBSTRATE

(2)



SC ELASTIC
2,4 kg/m²

or

(2)



SC ELASTIC EASY
2,4 kg/m²

48 - 72 HOURS

HORIZONTAL SURFACES
no primer required



PLANOCOLOR® PU



PLANOCOLOR® GRANULATES



PLANOEASY FINISH
(10% PU)

STONE CARPET
& WET AREAS
(1)

NOTES

(1) In places with permanent water presence, ensure proper inclination and drainage to avoid accumulation of standing water. Polyurethane resins have reduced acid resistance and excessive use of chemicals in wet areas, swimming pools and floors should be avoided.

(2) SC ELASTIC & SC ELASTIC EASY are suitable also for absorbent substrates.

SUBSTRATE PREPARATION



PLANOPRIMER

Water based acrylic primer for adhesion enhancement.

Consumption: 70 - 250 ml/m².

Packaging: 20L, 5L and 1L.



PLANO CONTACT FAST

Fast drying (receives covering in 15 - 60 minutes) quartz primer for non-absorbent surfaces.

Consumption: 300 - 400gr/m².

Packaging: 15Kg and 5Kg.



PLANOPRIMER EPOXY

Two component, solvent and water free, epoxy primer for absorbent and non absorbent substrates.

Consumption: 100 - 200 ml/m².

Packaging: (1,9 + 1,1) L.



WATERPRIMER EPX

Two component, water based, solvent free epoxy primer for absorbent substrates that require consolidation.

Consumption: 100 - 150 ml/m².

Packaging: (2 + 1)L.



SUBSTRATE PREPARATION



PLANO 120 S/F

Fast setting and hardening self-leveling compound for internal and external areas.

Consumption: 1,8 kg/m²/mm of thickness.

Packaging: 25Kg.



RC 220

One component multipurpose repairing mortar. Used for substrate levelling in a thickness of 2 - 20mm.

Consumption: 1,5 kg/m²/mm of thickness.

Packaging: 25Kg.



RC 240

One component multipurpose repairing and patching mortar. Used for substrate levelling in a thickness of 5 - 40mm.

Consumption: 1,8 kg/m²/mm of thickness.

Packaging: 25Kg.



NOVACEM RAPID FLOW

Fast setting and drying fluid mortar for levelling floors. Used for substrate levelling in a thickness of 20 - 80mm.

Consumption: 2,3 - 2,4 kg/m²/mm of thickness.

Packaging: 25kg.

SUBSTRATE PREPARATION



SC ELASTIC EASY

One component, cement-based, flexible waterproofing mortar. Suitable for absorbent and non-absorbent substrates.

Consumption: 1,2 kg/m²/mm.

Packaging: 20Kg.



SC ELASTIC

One component, cement-based, highly flexible waterproofing mortar. Suitable for absorbent and non-absorbent substrates.

Consumption: 1,2 kg/m²/mm of thickness.

Packaging: 20Kg.



SC 200 PENETRATE

Two component cement based waterproofing mortar for absorbent substrates.

Consumption: 1,6 kg/m²/mm of thickness.

Packaging: 25Kg (A) and 7L (B).



FIBERGLASS NET

Fiberglass net used for microcement or waterproofing compounds reinforcement, as well as for controlling the total layer thickness.

Packaging: 50 m².

DECORATIVE COATINGS



PLANOCOLOR AC

Acrylic resin binder ready to be mixed with colored granulates for creating decorative quartz plasters.

Consumption: Depending on the application.

Packaging: 5Kg.



PLANOCOLOR PU

Solvent-based polyurethane resin binder used for creating stone carpet floors.

Consumption: 0,2 - 1,0 L/m².

Packaging: 5L and 1L.



PLANOEASY GRIP

Admixture which is mixed with PLANOCOLOR PU binder, in order to create bonding primer, prior to the application of 'stone carpet' coverings, on vertical surfaces like in example staircases.

Consumption: Depending on the application.

Packaging: 50gr.



PLANOEASY FINISH

Special lubricant additive, to ease the application of stone carpet floors.

Consumption: Depending on the application.

Packaging: 1L.

PLANOCOLOR® GRANULATES



PLANOCOLOR GRANULATES MQ / MR / S

Natural uncoated granulates of marble (MR), quartz (MQ) and beige silica (S), suitable for creating PLANOCOLOR stone carpet, micro-pebble and terrazzo coverings.

Consumption: Depending on the type of application.

Packaging: Big bag, 25 kg.



PLANOCOLOR GRANULATES LC

Colored in the mass synthetic granulates, suitable for creating PLANOCOLOR stone carpet, micro-pebble and terrazzo coverings. Consumption: Depending on the type of application.

Packaging: 5 kg.



PLANOCOLOR GRANULATES RC GLASS

Colored granulates made of recycled glass. They are suitable for creating PLANOCOLOR terrazzo coverings and quartz plasters.

Consumption: Depending on the type of application.

Packaging: Big bag, 20 kg.



PLANOCOLOR GRANULATES NS / NXD / NXG

Coated granulates in various colors. Suitable for creating quartz plasters, after mixing with PLANOCOLOR AC binder.

Consumption: Depending on the type of application.

Packaging: 20 kg.

Edited by **Novamix**

Special thanks to for their photographic material

CMTC KUWAIT

www.cmtckuwait.com

EIRINI LUXURY VILLAS

www.eirinivillas.gr

NOUNIS SURFACES

www.nounis.gr

THALORI RETREAT

www.thalori.com

This edition published in 2022 by DOMOCHEMICAL S.A.

Copyright © 2022 DOMOCHEMICAL S.A.

No part of this publication may be reproduced, stored in a retrieval system or transmitted by any means, electronic, mechanical, photocopying or otherwise, without prior permission of the publisher.

Legal Notice: The technical data and recommendations included or listed are the outcome of laboratory measurements combined with our current knowledge and expertise. All information and specifications should in any case be considered as indicative. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications are subject to change without notice and may differ from product images. Due to printing and application procedures, the colors displayed here should be considered as indicative. In particular, variations in materials, substrates and on-site application conditions are such that no warranty can be given or implied reference to the suitability of the materials for trading or use for a particular purpose and conditions of any given project. Anyone interested in using the product must ensure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any outcomes associated with the use of product. Among other things, the Company is not responsible for any normal wear or tear from environmental or any other unsuitable conditions. We reserve the right to revise or change the data herein without prior notice. Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which has exclusive responsibility for providing technical advice and solutions, addressing relevant issues. Requests to the Technical Support Department are addressed and answered, only in writing. For the latest and valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr.



EN ISO 9001:2015



EN ISO 14001:2015

NOVAMIX.GR

12th Edition 04/2022



SCAN ME

DOMOCHEMICAL S.A.

40 PAPANIKOLI STR., CHALANDRI, 15232, ATHENS

T +30 210 68 93 953 F +30 210 68 94 571

FACTORY: 11TH KLM THIVA - CHALKIDA, THIVA

NOVAMIX@NOVAMIX.GR