

PAINT REMOVER GEL

Purpose paint remover

- ▷ **Removes paints, varnishes, coatings**
- ▷ **Gel, ideal for use on vertical surfaces**
- ▷ **Deep penetrating action**
- ▷ **Removes up to 10 layers in one application**

Description

PAINT REMOVER GEL is a powerful, all-purpose paint remover. It's a gel and makes it ideal for both vertical and horizontal surfaces. It is applied to mineral and building surfaces, metals, wood without corrosion. Its deep penetrating capacity makes it ideal for quick and easy removal of all types of paints, varnishes, plastic coatings, epoxy and polyurethane coatings. Usually only one application removes more than one layer of color. It contains no phenols and chlorinated hydrocarbons.

Uses

PAINT REMOVER GEL can be applied to facilitate stain removal in the following cases:

- Remove any type of paint, graffiti, etc.
- Enamel varnish and plastic coatings
- Residues of contact adhesive
- Epoxy and polyurethane dyes
- Lacquers, shellac, tar and many other coatings
- Residues of glue and epoxy grouts created during welding and grouting of ceramic tiles

Technical Data

Product Identity

Form	Gel
Color	Yellowish
Chemical Base	Mixture of solvents
Density	0,98 ± 0,05 kg/L

Application procedure

Application

Before applying PAINT REMOVER GEL, protect any surface that may be damaged when in contact with solvents. Apply PAINT REMOVER GEL as it is without thinning uniformly to a thick layer with a brush partially on surfaces of up to 0.5 m² at a time. When the coating has been softened (5 - 10 minutes) with a soft brush or cloth lightly rubbing the surface, remove the residue. At difficult points, repeat the process if necessary. Finally rinse the surface with cold water and detergent.

Recommendations

- Do not apply:
- Rubber, polystyrene, vinyl flooring, etc.
- It is not compatible with synthetic fabrics and fiberglass
- Do not use it in good quality wood without testing
- Avoid using in cases where the substrate and environment temperature less than +5°C or higher than +35°C
- Use only in a well-ventilated area
- Do not use it with hot air guns or near an open flame or other ignition source
- Keep out of reach of children

Consumption

Depending on the application 200 – 300 gr/m².

Storage

PAINT REMOVER GEL remains stable for at least 12 months from production date, in its sealed original packing, stored in dry conditions and temperatures between +5°C and +30°C.

Packaging

Containers of 1Kg

Safety Instructions

For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety related data.

Legal Notes

The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown.

In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product

must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice. Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr